



DEPENDABLE POWER

\$15483.60 inc gst

Super Series 05
Kubota Diesel

Stamford Alternator



Deep Sea Controls



Technical

Model	GK10S1
Type	Heavy Duty
Speed	1500 RPM
Phase/Voltage	1, 240
Frequency	50 Hz
Stdby Power kVA/kW	11kVA / 8.8kW
Prime Output kVA / kW	10kVA / 8.0kW
Noise Level (dBA @ 7m)	55dB(A)
Fuel Capacity	100 Litres

Engine

Manufacturer	Kubota Diesel
Engine Model	D1105-BG
Type & Cylinder	4 Stoke - 3 L
Induction	Naturally Aspirated
Fuel Consumption	2.3L @ 100%, 1.9L @ 75%, 1.4L @ 50% Load
Coolant Capacity	5.0 L
Governor	Mechanical
Cubic Capacity	1.123 L
Oil Capacity	5.1 L

Alternator

Alternator Brand / Model	Stamford PI044H
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

Canopy

Skid	Bunded fuel tank with fork lift pockets and skid tie down points
Canopy	Centre Lift, lockable doors with control panel viewing window
Paint Finish	Heavy duty powder coat finish white canopy with a black base
Emergency Stop	External Emergency Stop Fitted

Dimensions & Weight

Length	1.89m
Width	0.85m
Height	1.25m
Weight Dry	652 Kg

Controls

Controller	PLC 920 Auto/Manual Start with Analogue Metering
Circuit Breaker	Two Pole RCD MCBO
Battery Isolator	Fitted adjacent battery

Outlets

Outlets 3 Phase	N/A
Outlets 1 Phase	3 x 15amp IP66 with RCD MCBO
EBS (PMG)	Option

20804