

JKM330P-72

310-330 Watt

POLY CRYSTALLINE MODULE

Positive power tolerance of 0/+3%

ISO9001:2008、ISO14001:2004、OHSAS18001
certified factory.
IEC61215、IEC61730 certified products.

(4BB)



KEY FEATURES



4 Busbar Solar Cell:

4 busbar solar cell adopts new technology to improve the efficiency of modules, offers a better aesthetic appearance, making it perfect for rooftop installation.



High Efficiency:

High module conversion efficiency (up to 17.01%), through innovative manufacturing technology.



Low-light Performance:

Advanced glass and solar cell surface texturing allow for excellent performance in low-light environments.



Severe Weather Resilience:

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).




Durability against extreme environmental conditions:


High salt mist and ammonia resistance certified by TUV NORD.

LINEAR PERFORMANCE WARRANTY

10 Year Product Warranty • 25 Year Linear Power Warranty



Engineering Drawings




Packaging Configuration

(Two pallet=One stack)

25pcs/pallet, 50pcs/stack, 600 pcs/40'HQ Container

Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	Poly-crystalline 156×156mm (6 inch)
No. of cells	72 (6×12)
Dimensions	1956×992×40mm (77.01×39.05×1.57 inch)
Weight	26.5 kg (58.4 lbs.)
Front Glass	4.0mm, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67 Rated
Output Cables	TÜV 1×4.0mm ² ; Length: 900mm or Customized Length

SPECIFICATIONS

Module Type	JKM310P		JKM315P		JKM320P		JKM325P		JKM330P	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	310Wp	230Wp	315Wp	233Wp	320Wp	237Wp	325Wp	241Wp	330Wp	245Wp
Maximum Power Voltage (Vmp)	37.0V	34.4V	37.2V	34.7V	37.4V	34.7V	37.6V	35.0V	37.8V	35.3V
Maximum Power Current (Imp)	8.38A	6.68A	8.48A	6.71A	8.56A	6.83A	8.66A	6.89A	8.74A	6.94A
Open-circuit Voltage (Voc)	45.9V	42.7V	46.2V	42.8V	46.4V	43.0V	46.7V	43.3V	46.9V	43.6V
Short-circuit Current (Isc)	8.96A	7.26A	9.01A	7.28A	9.05A	7.35A	9.10A	7.40A	9.14A	7.45A
Module Efficiency STC (%)	15.98%		16.23%		16.49%		16.75%		17.01%	
Operating Temperature(°C)	-40°C~+85°C									
Maximum system voltage	1000VDC (IEC)									
Maximum series fuse rating	15A									
Power tolerance	0~+3%									
Temperature coefficients of Pmax	-0.41%/°C									
Temperature coefficients of Voc	-0.31%/°C									
Temperature coefficients of Isc	0.06%/°C									
Nominal operating cell temperature (NOCT)	45±2°C									

STC: Irradiance 1000W/m² Cell Temperature 25°C AM=1.5

NOCT: Irradiance 800W/m² Ambient Temperature 20°C AM=1.5 Wind Speed 1m/s

* Power measurement tolerance: ± 3%